SWISS-PARK

A LÖDIGE INDUSTRIES COMPANY

# SEMI-AUTOMATED PARKING SYSTEM - MAX3



## Technical data sheet

- ✓ CE certified
- ✓ Space saving
- ✓ Independent parking
- ✓ Low maintenance cost
- ✓ Flexible parking
- ✓ Low noise

SWISS-PARK
A LÖDIGE INDUSTRIES COMPANY

**Lödige Industries GmbH** | Balhorner Feld 1
33106 Paderborn | Germany | Phone: +49 5251 2980-0
e-mail: info@lodige.com | www.lodige.com



# Max3 (Max3-R)


## ► Semi-automated parking system




## Dimensions

- All dimensions specified are the minimum, finished dimensions.
- Tolerances for the dimensions $^{+3}_{0}$. (1)
- Dimensions are in cm.
- Evenness of the carriageway floor are strictly in accordance with DIN 18202, chart 3, line 3.

### Standard passenger car (L)




### Standard station wagon (K)





Standard passenger cars are vehicles without any sports options such as spoilers, low-profile tyres, etc.

## Parking possibilities


| | Standard Max3 | Reinforced Max3-R |
|---|---|---|
| **Width** in cm | 190 (2) | 190 (2) |
| **Weight** in kg | max. 2000 | 2600 |
| **Wheel load** in kg | max. 500 | 650 |

## Height dimensions

All pit and height variants can be found on page 2.




Smallest version





Largest version

## ► Specification

- Independent parking
- Grid arrangement
  - ► Minimum 2 grids for 5 vehicles
  - ► Maximum 10 grids
- Car heights = 150 cm to 220 cm
- Car length = 500 cm to 520 cm
- **Max3 (Standard) :** Load capacity = 2000 kg per parking place, Usable platform width up to 270 cm
- **Max3-R (Reinforced) :** Load capacity = 2600 kg per parking place. Usable platform width up to 270 cm

## ► Garage without door




## ► Notes

(1) To comply with the minimum finished dimensions, the tolerances according to VOB, Part C (DIN 18330 and 18331) and DIN 18202 must also be considered.

(2) Car width for 230 cm platform width. For the greatest possible ease of use, we recommend platform widths of 250 to 270 cm. If wider platforms are used, it is possible to park wider cars.

(3) Dimension depends on the type and size of the door. In accordance with DIN EN 14010, the doors should be selected.

(4) Grounding of the system to be connected to the central grounding on-site (to be provided by customer).

(5) At the transition section between the pit floor and walls, no hollow mouldings/coves are possible. If hollow mouldings/coves are required, the systems must be designed smaller or the pits accordingly wider.

(6) Drainage sump : 10 x 2 cm with 50 x 50 x 50 cm drainage pit, install a sump pump (refer to manufacturer's dimensions).

(7) These floor areas need to be horizontal and on equal levels across the full width of the pit.

(8) For comfortable use of your parking space and to accommodate longer cars, we recommend a pit length of 570 cm.

⚠ If sprinklers are required make sure to provide the necessary free spaces during the planning stage.




**Page 1** Sections, dimensions, car data
**Page 2** Variants and Height dimensions
**Page 3** Width dimensions
**Page 4** Width dimensions, wall clearance
**Page 5** Numbering, Function, Approach,
**Page 6** Load plan, Space for duct installation
**Page 7** Electrical installation, Detail hydraulic unit
**Page 8** Technical hint
**Page 9** Facilities from customer
**Page 10** Description
**Page 11** Description

**Lödige Industries GmbH** | Balhorner Feld 1
33106 Paderborn | Germany | Phone: +49 5251 2980-0
e-mail: info@lodige.com | www.lodige.com



**Page 1** Sections, dimensions, car data
**Page 2** Variants and Height dimensions
**Page 3** Width dimensions
**Page 4** Width dimensions, wall clearance
**Page 5** Numbering, Function, Approach,
**Page 6** Load plan, Space for duct installation
**Page 7** Electrical installation, Detail hydraulic unit
**Page 8** Technical hint
**Page 9** Facilities from customer
**Page 10** Description
**Page 11** Description

## ▶ Overview of parking system variants and building heights




| Max3 Type | Pit depth (PD) | Vehicle height (LF) | Building Height (H) | | | Vehicle height (GF) | Vehicle height (UF) | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | 150 | 155 | 160 | 165 | 170 | 175 | 180 | 185 | 190 | 195 | 200 | 205 | Building Height (H) |
| Max3-175 | 175 | 150 | 345 | 365 | 380 | 150 | 325 | | | | | | | | | | | | |
| | | | | | | 155 | 330 | 335 | | | | | | | | | | | |
| | | | | | | 160 | 335 | 340 | 345 | | | | | | | | | | |
| | | | | | | 165 | 340 | 345 | 350 | 355 | | | | | | | | | |
| | | | | | | 170 | 345 | 350 | 355 | 360 | 365 | | | | | | | | |
| | | | | | | 175 | 350 | 355 | 360 | 365 | 370 | 375 | | | | | | | |
| | | | | | | 180 | 355 | 360 | 365 | 370 | 375 | 380 | | | | | | | |
| | | | | | | 185 | 360 | 365 | 370 | 375 | 380 | | | | | | | | |
| | | | | | | 190 | 365 | 370 | 375 | 380 | | | | | | | | | |
| | | | | | | 195 | 370 | 375 | 380 | | | | | | | | | | |
| | | | | | | 200 | 375 | 380 | | | | | | | | | | | |
| | | | | | | 205 | 380 | | | | | | | | | | | | |
| Max3-200 | 200 | 175 | 375 | 405 | | 175 | 350 | 355 | 360 | 365 | 370 | 375 | | | | | | | |
| | | | | | | 180 | 355 | 360 | 365 | 370 | 375 | 380 | 385 | | | | | | |
| | | | | | | 185 | 360 | 365 | 370 | 375 | 380 | 385 | 390 | 395 | | | | | |
| | | | | | | 190 | 365 | 370 | 375 | 380 | 385 | 390 | 395 | 400 | 405 | | | | |
| | | | | | | 195 | 370 | 375 | 380 | 385 | 390 | 395 | 400 | 405 | | | | | |
| | | | | | | 200 | 375 | 380 | 385 | 390 | 395 | 400 | 405 | | | | | | |
| | | | | | | 205 | 380 | 385 | 390 | 395 | 400 | 405 | | | | | | | |
| Max3-230 | 230 | 205 | 435 | | | 205 | 380 | 385 | 390 | 395 | 400 | 405 | 410 | 415 | 420 | 425 | 430 | 435 | |

**The permitted vehicle height on the ground floor must be greater than or equal to the vehicle height on the upper and lower floor!**


**Lödige Industries GmbH** | Balhorner Feld 1
33106 Paderborn | Germany | Phone: +49 5251 2980-0
e-mail: info@lodige.com | www.lodige.com



**Page 1** Sections, dimensions, car data
**Page 2** Variants and Height dimensions
**Page 3** Width dimensions
**Page 4** Width dimensions, wall clearance
**Page 5** Numbering, Function, Approach,
**Page 6** Load plan, Space for duct installation
**Page 7** Electrical installation, Detail hydraulic unit
**Page 8** Technical hint
**Page 9** Facilities from customer
**Page 10** Description
**Page 11** Description

# ► Width dimensions


## ► Sliding door behind columns




| | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| **Max. car height (UF & GF)** | 150 | 155 | 160 | 165 | 170 | 175 | 180 | 185 | 190 | 195 |
| **Drive through height (H1)** | 210 | 210 | 210 | 210 | 210 | 210 | 210 | 210 | 210 | 210 |

| | | |
|---|---|---|
| **Max. car height (UF & GF)** | 200 | 205 |
| **Drive through height (H1)** | 220 | 220 |


## ► Sliding door in front of columns




| | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| **Max. car height (UF & GF)** | 150 | 155 | 160 | 165 | 170 | 175 | 180 | 185 | 190 | 195 |
| **Drive through height (H1)** | 210 | 210 | 210 | 210 | 210 | 210 | 210 | 210 | 210 | 210 |


| | | |
|---|---|---|
| **Max. car height (UF & GF)** | 200 | 205 |
| **Drive through height (H1)** | 220 | 220 |

### Columns per each grid unit





| usable platform width | Grid width (RB) | Garage width | |
|---|---|---|---|
| | | B1 | B2 |
| 230 | 250 | 250 | 230 |
| 240 | 260 | 260 | 240 |
| **250** | **270** | **270** | **250** |
| **260** | **280** | **280** | **260** |
| **270** | **290** | **290** | **270** |

### Columns every second grid unit





| usable platform width | Grid width (RB) | Garage width | |
|---|---|---|---|
| | | B3 | B4 |
| 230 | 250 | 500 | 480 |
| 240 | 260 | 520 | 500 |
| **250** | **270** | **540** | **520** |
| **260** | **280** | **560** | **540** |
| **270** | **290** | **580** | **560** |

### Columns per each grid unit




| usable platform width | Grid width (RB) | Garage width | |
|---|---|---|---|
| | | B1 | B2 |
| 230 | 250 | 250 | 230 |
| 240 | 260 | 260 | 240 |
| **250** | **270** | **270** | **250** |
| **260** | **280** | **280** | **260** |
| **270** | **290** | **290** | **270** |

### Columns every second grid unit




| usable platform width | Grid width (RB) | Garage width | |
|---|---|---|---|
| | | B3 | B4 |
| 230 | 250 | 500 | 480 |
| 240 | 260 | 520 | 500 |
| **250** | **270** | **540** | **520** |
| **260** | **280** | **560** | **540** |
| **270** | **290** | **580** | **560** |

SWISS-PARK
A LÖDIGE INDUSTRIES COMPANY


**Lödige Industries GmbH** | Balhorner Feld 1
33106 Paderborn | Germany | Phone: +49 5251 2980-0
e-mail: info@lodige.com | www.lodige.com



**Page 1** Sections, dimensions, car data
**Page 2** Variants and Height dimensions
**Page 3** Width dimensions
**Page 4** Width dimensions, wall clearance
**Page 5** Numbering, Function, Approach,
**Page 6** Load plan, Space for duct installation
**Page 7** Electrical installation, Detail hydraulic unit
**Page 8** Technical hint
**Page 9** Facilities from customer
**Page 10** Description
**Page 11** Description

## ► Width dimensions


### ► Sliding door between columns




| Max. car height (UF & GF) | 150 | 155 | 160 | 165 | 170 | 175 | 180 | 185 | 190 | 195 |
|---|---|---|---|---|---|---|---|---|---|---|
| Drive through height (H1) | 220 | 220 | 220 | 220 | 220 | 220 | 220 | 220 | 220 | 220 |

| Max. car height (UF & GF) | 200 | 205 |
|---|---|---|
| Drive through height (H1) | 230 | 230 |

### ► Roller shutter





| Max. car height (UF & GF) | 150 | 155 | 160 | 165 | 170 | 175 | 180 | 185 | 190 | 195 |
|---|---|---|---|---|---|---|---|---|---|---|
| Drive through height (H1) | 210 | 210 | 210 | 210 | 210 | 210 | 210 | 210 | 210 | 210 |

| Max. car height (UF & GF) | 200 | 205 |
|---|---|---|
| Drive through height (H1) | 220 | 220 |

### Columns per each grid unit


**Option not possible!**

### Columns every second grid unit





| usable platform width | Grid width (RB) | Garage width | |
|---|---|---|---|
| | | B3 | B4 |
| 230 | 250 | 500 | 480 |
| 240 | 260 | 520 | 500 |
| **250** | **270** | **540** | **520** |
| **260** | **280** | **560** | **540** |
| **270** | **290** | **580** | **560** |

### Columns per each grid unit




| usable platform width | Grid width (RB) | Garage width | |
|---|---|---|---|
| | | B1 | B2 |
| 230 | 250 | 250 | 230 |
| 240 | 260 | 260 | 240 |
| **250** | **270** | **270** | **250** |
| **260** | **280** | **280** | **260** |
| **270** | **290** | **290** | **270** |

## ► Wall clearance




We recommend platform widths of a minimum of 270 cm for edge boxes and boxes with partitions and driving lane widths of 650 cm so that vehicles can comfortably enter and leave the **swiss-park**-systems without difficulty.

Narrower platforms may impede parking according to the following criteria.

- Driving lane width
- Entrance conditions
- Vehicle dimensions


9 Observe minimum driving lane width in accordance with local regulations!

**Lödige Industries GmbH** | Balhorner Feld 1
33106 Paderborn | Germany | Phone: +49 5251 2980-0
e-mail: info@lodige.com | www.lodige.com



## ▶ Numbering

The standard numbering of the car parking space is as follows:




In the default setting the basement platform no. 2 is raised to entrance level (Cover of the pit according to safety regulations).

Different numbering is only possible at extra charge.

Please take note of the following specifications:


- In general, the empty space must be arranged to the left.
- The numbers must be provided 8 – 10 weeks before the delivery date.

## ▶ Function


### Example :


**For accessing parking space No. 8:**

- Check first that all doors are closed, then select No. 8 on operating panel.
- For driving the vehicle off platform No. 8 the upper parking platforms are shifted to the left.
- The empty space is now above the vehicle which shall be driven off the platform. The platform No. 8 will be raised.
- The vehicle on platform No. 8 can now be driven off the platform.




## ▶ Approach




The illustrated maximum approach angles must not be exceeded.

Incorrect approach angles will cause serious manoeuvring and positioning problems on the parking system for which the company **Lödige Industries** accepts no responsibility.

**Page 1** Sections, dimensions, car data
**Page 2** Variants and Height dimensions
**Page 3** Width dimensions
**Page 4** Width dimensions, wall clearance
**Page 5** Numbering, Function, Approach,
**Page 6** Load plan, Space for duct installation
**Page 7** Electrical installation, Detail hydraulic unit
**Page 8** Technical hint
**Page 9** Facilities from customer
**Page 10** Description
**Page 11** Description

**Lödige Industries GmbH** | Balhorner Feld 1
33106 Paderborn | Germany | Phone: +49 5251 2980-0
e-mail: info@lodige.com | www.lodige.com




**Page 1** Sections, dimensions, car data
**Page 2** Variants and Height dimensions
**Page 3** Width dimensions
**Page 4** Width dimensions, wall clearance
**Page 5** Numbering, Function, Approach,
**Page 6** Load plan, Space for duct installation
**Page 7** Electrical installation, Detail hydraulic unit
**Page 8** Technical hint
**Page 9** Facilities from customer
**Page 10** Description
**Page 11** Description

## ► Load plan

- The semi-automated parking systems are anchored into the ground. The drill hole depth on the floor is approx. 15 cm, and on the walls approx. 12 cm.
- Floor and walls below the drive-in level must be made of concrete (concrete quality min. C20/25)!
- The dimensions of the load-bearing points are approximate. If the exact dimensions are required, please consult **Lödige Industries.**


### Side view :

#### MAX3-175





| Height | Vehicle height (GF) | H3 | H4 |
|---|---|---|---|
| 345 | 170 | 150 | 265 |
| 265 | 190 | 170 | 285 |
| 365 | 170 | 150 | 265 |
| 380 | 205 | 185 | 300 |
| 405 | 190 | 170 | 285 |
| 435 | 205 | 185 | 300 |

#### MAX3-200





| Height | Vehicle height (GF) | H3 | H4 |
|---|---|---|---|
| 365 | 190 | 155 | 270 |
| 375 | 175 | 155 | 270 |
| 380 | 205 | 185 | 300 |
| 405 | 205 | 185 | 300 |
| 435 | 205 | 185 | 300 |

#### MAX3-230




| Height | Vehicle height (GF) | H3 | H4 |
|---|---|---|---|
| 380 | 205 | 185 | 300 |
| 405 | 205 | 185 | 300 |
| 435 | 205 | 185 | 300 |

### Top view :





| usable platform width | Grid width | | |
|---|---|---|---|
| | RB | RB1 | RB2 |
| 230 | 250 | 260 | 135 |
| 240 | 260 | 270 | 140 |
| 250 | 270 | 280 | 145 |
| 260 | 280 | 290 | 150 |
| 270 | 290 | 300 | 155 |

| Platform load | Force (kN) | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | F1 | F2 | F3 | F4 | F5 | F6 | F7 | F8 | F9 |
| 2000 kg | ±5 | ±2,5 | ±14,5 | +70 | ±29 | ±0,2 | ±2,5 | +25 | +50 |
| 2600 kg | ±5 | ±2,5 | ±14,5 | +80 | ±29 | ±0,2 | ±2,5 | +35 | +70 |

⑩ Height dimensions (see **"Overview of parking system variants and building heights"**, Page 2)

## ► Space for duct installation





⑪ For dimension RB, see **"Width dimensions"**, pages 3 and 4.

**Lödige Industries GmbH** | Balhorner Feld 1
33106 Paderborn | Germany | Phone: +49 5251 2980-0
e-mail: info@lodige.com | www.lodige.com



## ▶ Electrical installation




**Electrical data** to be performed by the customer


| No. | Qty. | Description | Position | Frequency |
|---|---|---|---|---|
| 1 | 1 | Electricity meter | in the supply line | |
| 2 | 1 | Main fuse: 3 x fuse 16 A (slow) or circuit breaker 3 x 16 A (trigger characteristic K or C) | in the supply line | 1 per 3,0 kW unit |
| 3 | 1 | Supply line 5 x 2.5 mm² (3 PH + N + PE) with marked wire and protective conductor | to main switch | 1 per unit |
| 4 | 1 | Supply line 5 x 2,5 mm² (3 PH + N + PE) with marked wire and protective conductor | from main switch to unit | 1 per unit |
| 5 | 1 | Lockable main switch | defined at the plan check | 1 per unit |
| 6 | every 10 m | Foundation earth connector | corner pit floor | |
| 7 | 1 | Potential equalization from foundation grounding connection system according to DIN EN 60204 | | 1 per system |

**Electrical data** included in delivery of **Lödige Industries**


| No. | Designation |
|---|---|
| 8 | Junction box unit |
| 9 | Control line 4 x 2,5 mm² with marked wire and protective conductor |
| 10 | Hydraulic unit 3,0 kW, three phase current, 230/400 V, 50 Hz |
| 11 | Control line 4 x 1 mm² with marked wire and protective conductor |
| 12 | Operating device |
| 13 | Control line 3 x 1 mm² (PH + N + PE) |

### Control box

The control box must be accessible at all times from outside! Dimensions approx. 100 x 100 x 30 cm.
Cutting through of wall from control box to parking system (contact **Lödige Industries** for clarification).




## ▶ Detail building construction – foundation hydraulic unit




If the installation of the hydraulic power pack is not possible in adjacent room or building, the hydraulic power pack and the electrical components must be accommodated in a cabinet (at an additional cost).

The cabinet is to be planned in the rear area of the parking system. For this purpose, a foundation (140 x 60 cm) made of concrete is required (concrete quality min. C20/C25). The cabinet is dowelled into the floor. The drill hole depth is approx. 10 cm.

⑫ Free space

**Page 1** Sections, dimensions, car data
**Page 2** Variants and Height dimensions
**Page 3** Width dimensions
**Page 4** Width dimensions, wall clearance
**Page 5** Numbering, Function, Approach,
**Page 6** Load plan, Space for duct installation
**Page 7** Electrical installation, Detail hydraulic unit
**Page 8** Technical hint
**Page 9** Facilities from customer
**Page 10** Description
**Page 11** Description

**Lödige Industries GmbH** | Balhorner Feld 1
33106 Paderborn | Germany | Phone: +49 5251 2980-0
e-mail: info@lodige.com | www.lodige.com



## ▶ Technical hint

### Usage area
As a standard, the system is suitable for fixed number of users. If different users (e.g., short-term parking in office buildings or hotels), the **swiss-park** system requires modifications. Feel free to contact us for consultation.

### Units
Low-noise hydraulic units mounted on Anti-vibration mounting plates are installed. But, we also recommend separating the garage body from the residential building. If it is not possible to install the hydraulic unit in adjacent buildings or rooms, the hydraulic unit and the electrical components must be housed in a cabinet (at an additional cost) (see **"Detail building construction – foundation hydraulic unit"**, page 7).

### CE certification
The systems offered correspond to DIN EN 14010 and the EC Machinery Directive 2006/42/EC.

### Building application documents
According to LBO and GaVo (garage regulations), the **swiss-park** systems are subject to approval. Please observe the local rules and regulations.

### Available documents
- Wall recess plans
- Maintenance offer/contract
- Declaration of conformity

### Environmental conditions
Ambient conditions for the areas around the semi-automated parking system:

- Temperature range -10 °C to +40 °C
- Relative humidity of 50% at a maximum outside temperature of +40 °C.

The lifting and lowering of the parking systems are calculated at an ambient temperature of +10 °C and with the hydraulic system positioned immediately adjacent to the parking system. The operating time of parking system increases at lower ambient temperatures or with longer hydraulic lines.

### Care & Protection
To avoid corrosion damage, please follow separate cleaning and care instructions (as per the **"Corrosion protection"** sheet) and ensure that your garage is well ventilated.

### Noise protection
**Standard noise protection:**

As per DIN 4109-1 (Sound insulation in buildings – Part 1: Minimum requirements) - Section 9:

- Maximum noise level in living and sleeping areas 30 dB (A).

Noise created by users is not considered.

The following dimensions are required for adherence to this value:

- Noise protection package in accordance with quote/order (**Lödige Industries**).
- Noise insulation dimension of the building structure of minimum weighted sound reduction index, min. R'w = 57 dB (service to be provided by the customer)

**Increased noise protection (special agreement):**

As per DIN 4109-5 (Sound insulation in buildings - Part 5: Increased requirements) - Section 8:

- Maximum noise pressure level in living and sleeping areas 25 dB (A).

Noise created by users is not considered.

The following dimensions are required for adherence to this value:

- Noise protection package in accordance with quote/order (**Lödige Industries**).
- Noise insulation dimension of the building structure of min. R'w = 62 dB (service to be provided by the customer)

**HINT** : User noises are the noises that can be influenced by individual users of our **swiss-park** systems. These are created during the accessing of the platform, slamming of vehicle doors, engine, and brake noise.

**Page 1** Sections, dimensions, car data
**Page 2** Variants and Height dimensions
**Page 3** Width dimensions
**Page 4** Width dimensions, wall clearance
**Page 5** Numbering, Function, Approach,
**Page 6** Load plan, Space for duct installation
**Page 7** Electrical installation, Detail hydraulic unit
**Page 8** Technical hint
**Page 9** Facilities from customer
**Page 10** Description
**Page 11** Description

**Lödige Industries GmbH** | Balhorner Feld 1
33106 Paderborn | Germany | Phone: +49 5251 2980-0
e-mail: info@lodige.com | www.lodige.com



**Page 1** Sections, dimensions, car data
**Page 2** Variants and Height dimensions
**Page 3** Width dimensions
**Page 4** Width dimensions, wall clearance
**Page 5** Numbering, Function, Approach,
**Page 6** Load plan, Space for duct installation
**Page 7** Electrical installation, Detail hydraulic unit
**Page 8** Technical hint
**Page 9** Facilities from customer
**Page 10** Description
**Page 11** Description

## ▶ Facilities to be provided by the customer

### Safety barriers
During construction of the semi-automated parking system, in accordance with DIN EN ISO 13857, safety barriers are to be placed immediately in front of, adjacent to, or behind the systems where there are roadways.

### Parking space numbering
Parking space numbering, if required.

### Building services
Ventilation, fire extinguishing and fire alarm systems, as well as clarification and compliance with the relevant regulatory requirements.

### Lighting
The customer must observe local regulations pertaining to the illumination of parking spaces and roadways. In accordance with DIN EN 12464-1 'Light and lighting - Lighting of work places', an illumination level of min. 200 lx is recommended for the parking spaces and operating area of the system.

### Drainage
For the front area of the pit, we recommend a drainage channel, which you connect to a floor drain system or sump (50 x 50 x 20 cm). The drainage channel may be inclined to the side, however not the pit floor itself (longitudinal incline is available). For reasons of environmental protection, we recommend painting the pit floor, and to provide oil and petrol separators in the connections to the public sewage network.

### Wall cutout
Any necessary wall cutout to be provided by the customer.

### Strip footings
If due to structural conditions strip footings must be effected, the customer shall provide an accessible platform reaching to the top of the said strip footings to enable and facilitate the mounting work.

### Electrical supply to the main switch / Foundation earth connector
The customer must lay the supply cable to the master switch during assembly. Functional capability can be checked by our engineers on-site, in conjunction with the electrical engineer. If this is not possible during assembly for reasons attributable to the customer, the customer must commission an electrical engineer.


The customer must earth the steel structure with a foundation earth connection (earthing distance max. 10 m) and equipotential bonding in accordance with DIN EN 60204 (see **"Electrical installation"**, page 7)

### Door suspensions
Lintel height "H1" (see **"Width dimensions"**, pages 3 and 4) specified by us are absolutely necessary. With differing heights, additional measures for door attachment (door suspensions) are done at extra cost.


### Safety enclosure shields
Safety enclosure shields are necessary if there are any gap between the door and side walls. If desired, they can be ordered from **Lödige Industries** for an additional charge.

### Control panel
Empty conduits and recesses for the operating element (see **"Electrical installation"**, page 7). Consultation with **Lödige Industries** is required when using folding doors.

**Control panel on plaster**




**Control panel under plaster**




### Other services on-site
- Preparation of the parking system pit
- Measures for the implementation of water protection regulations
- Measures to comply with fire protection regulations and noise protection in accordance with DIN4109
- Pit measurement
- Daily update on project photos, if required.
- Foundation grounding if necessary
- All permits and approvals

### If the following are not included in the quotation, they will also have to be provided/paid for by the customer:
- Mounting of contactor and terminal box to the wall valve, complete wiring of all elements in accordance with the circuit diagram
- Costs for final technical approval by an authorized body
- Main switch
- Control line from main switch to hydraulic unit

**Lödige Industries GmbH** | Balhorner Feld 1
33106 Paderborn | Germany | Phone: +49 5251 2980-0
e-mail: info@lodige.com | www.lodige.com



# ▶ Description - Semi-automated parking system

## General description

- **swiss-park** systems are for independent parking spaces for cars, one on top of the other and side by side.
- Dimensions according to the underlying pit, width and height dimensions
- The pitches are driven horizontally and have a gradient of ±1° for proper drainage of the platforms.
- Along the complete width of the **swiss-park** system, an approach lane (driving lane in accordance with local regulations) must be available.
- The platforms of both the lower floor (LF) and upper floor (UF) are moved vertically and the platforms of the ground floor (GF) horizontally. At approach level (GF) there is always one parking space less. This vacant space is used for shifting the ground floor (GF) parking spaces sideways, thus enabling an upper floor (UF) parking space or lower floor (LF) parking space to be lowered or lifted to approach level. Consequently, a unit of five parking spaces (2 on the upper floor, 1 on the ground floor, 2 on the lower floor) is the smallest unit available for this parking system.
- For safety reasons, the platforms can only be moved behind electromagnetically locked doors.
- All necessary safety devices are installed. This consists mainly of a chain monitoring system, locking lever for the upper and lower platforms and electromagnetic door locks. The doors can only be opened if the selected parking space has reached the park position and all openings are secured.
- Fixing the control element usually in front of the support or on the way revealing the outside.
- Operating instructions at every operating point.

## swiss-park system consisting of:

- Seriated supports
- Steel pillars with sliding platform support
- Cross and longitudinal members
- running rails for the transversely movable ground floor (GF) platforms
- Hydraulic cylinders
- Dowels, screws, fasteners, connecting elements etc.

## Platform consisting of:

- Platform profiles
- Adjustable positioning aids
- Bevelled bumpers
- Lateral beams
- Brackets
- Screws, nuts, spacer tubes, etc.

## Lifting device for upper floor (UF) and lower floor (LF) platforms consisting of:

- Hydraulic cylinder with solenoid valve
- Chain wheels
- Chains
- Limit switches
- The platforms are suspended on four points and guided along the supports using plastic sliding bearings.

## Drive unit of transversely movable platforms on the ground floor (GF) consisting of:

- Gear motor with chain wheel
- Chains
- Running and guide rollers (low-noise)
- Power supply via cable chain

## Roller shutters:

**Size**
Dimensions adapted to the underlying width and height dimensions.

**Curtain/door profile**

- Steel pipe
- End rod with electronic contact strip
- painted version

**Gate operation**

- Electric drive by means of a tubular motor in the shaft.
- For safety reasons, the platforms are always moved behind locked gates.
- The positions “gate open” and “gate closed” are monitored by electrical signal transmitters.

## Sliding doors:

**Size**

- Sliding door, dimensions: approx. 2500 mm x 2000 mm (width x height).

**Frame**

- Frame construction with vertical centre stay bar made from steel pipe.

**Standard door panel**

- Wire mesh: Mesh size 50 x 50 x 3.8 mm

**Page 1** Sections, dimensions, car data
**Page 2** Variants and Height dimensions
**Page 3** Width dimensions
**Page 4** Width dimensions, wall clearance
**Page 5** Numbering, Function, Approach,
**Page 6** Load plan, Space for duct installation
**Page 7** Electrical installation, Detail hydraulic unit
**Page 8** Technical hint
**Page 9** Facilities from customer
**Page 10** Description
**Page 11** Description

**Lödige Industries GmbH** | Balhorner Feld 1
33106 Paderborn | Germany | Phone: +49 5251 2980-0
e-mail: info@lodige.com | www.lodige.com



**Running rails**

- The running gear of each door consists of 2 twin-pair rolling gadgets, adjustable in height.
- The running rails of the doors are fixed to brackets or the concrete lintel, or on a building-specific door suspension using ceiling fittings.
- The guide consists of 2 plastic rollers mounted to a base plate, which is dowelled to the floor.
- Running rails, ceiling fittings and guide roller base plates are hot-dip galvanized.

**Door actuation**

Standard:

- Manually, i.e. the door is opened and closed by hand.

Alternatively:

- Electric drive via electric motor mounted to the rail system at the turning point of the sliding doors.
- The drive pinion engages into the chain mounted to the door.

For safety reasons, the movement of the platforms is always made behind locked doors. Position sensing, i.e. “door open” and “door closed” is effected by electric signals.

**Separation (if necessary)**:

- Upon request

**Please note**:

Door panels (on the side, cover for running rails, etc.) and door suspensions are not included in the standard version but can be delivered against surcharge as special equipment.

## Control system consisting of:

- Central control cabinet (operating device) used to select the desired parking space.
- With series installation, the doors are opened manually. If desired, this can also be done using electric motors.
- Electric wiring is made from the electric cabinet by the manufacturer.

## Hydraulic unit consisting of:

- Hydraulic unit (low noise, installed onto a console with a rubber-bonded-to-metal mounting)
- Hydraulic oil tank
- Oil filling
- Internal gear pump
- Pump holder
- Coupling
- Three-phase motor (3.0 kW, 230/400 V, 50 Hz)
- Pressure gauge
- Pressure relief valve
- Hydraulic hoses (to reduce noise transmission to the hydraulic pipes)

## We reserve the right to change these specifications without notice!

**Lödige Industries** reserves the right, in the course of technical and technological progress, to use newer or different technologies, systems, processes, procedures, or standards than those originally offered and ensure that the customer does not incur any disadvantage.

**Page 1** Sections, dimensions, car data
**Page 2** Variants and Height dimensions
**Page 3** Width dimensions
**Page 4** Width dimensions, wall clearance
**Page 5** Numbering, Function, Approach,
**Page 6** Load plan, Space for duct installation
**Page 7** Electrical installation, Detail hydraulic unit
**Page 8** Technical hint
**Page 9** Facilities from customer
**Page 10** Description
**Page 11** Description


SWISS-PARK
A LÖDIGE INDUSTRIES COMPANY